

Earth Resistance Clamp Meter

CE-8201

HTCTM
INSTRUMENTS

Features:

- 0.01Ω High Accuracy for low resistance measurement
- Data Logging up to 99 groups
- Alarm Threshold setting from 1Ω to 100Ω
- Leakage Current measurement from 0.1mA to 20A



Technical Data :

Basic Functions	Range	Resolution	Basic Accuracy
Resistance	0.01 Ω ~ 0.999 Ω	0.001 Ω	±(1.5%+0.01Ω)
	1 Ω ~ 9.99 Ω	0.01 Ω	±(1.5%+0.1Ω)
	10 Ω ~ 99.9 Ω	0.1 Ω	±(2.0%+0.3Ω)
	100 Ω ~ 199.9 Ω	1 Ω	±(3.0%+1Ω)
	200 Ω ~ 400 Ω	5 Ω	±(6.0%+5Ω)
	400 Ω ~ 600 Ω	10 Ω	±(10%+10Ω)
	600 Ω ~ 1200 Ω	20 Ω	Approx 20%
Current	100mA	0.1mA	±(2.5%+1mA)
	300mA	0.3mA	±(2.5%+2mA)
	1A	0.001 A	±(2.5%+0.003A)
	3A	0.003 A	±(2.5%+0.01A)
	10A	0.01 A	±(2.5%+0.03A)
	20A	0.03 A	±(2.5%+0.05A)

- **Standard Accessory** : Battery, Hard Carrying Case, Manual
- **Dimension** : 275 (H) * 110 (W) * 54 (D) MM
- **Weight** : 1032 gm