

**CM-2090**

**Features:**

- SMART AC Digital Flexible Clamp.
- Ø 75mm.
- 6,000 Counts.

**DC VOLTAGE**

Range	Resolution	Accuracy
6V	0.001V	±0.8% of rdg + 3 digits
60V	0.01V	
600V	0.1V	

**AC VOLTAGE**

Range	Resolution	Accuracy	
		45 - 65Hz	40 - 2000Hz
6V	0.001V	± 1.2% of rdg + 3 digits	± 2.0% of rdg + 5 digits
60V	0.01V		
600V	0.1V		

**FREQUENCY**

Range	Resolution	Accuracy
40 - 1000Hz	0.1Hz	±0.5% of rdg + 2 digits
1kHz - 10KHz	1Hz	

**AC CURRENT**

Range	Resolution	Accuracy		
		40 - 65Hz	65 - 400Hz	400-1, 000Hz
60A	0.01A	± 3.0% of rdg + 5 digits	± 3.0% of rdg + 5 digits	-
600A	0.1A			
3000A	1A			

- Standard Accessories : Soft Carrying Case, Test Lead, Manual
- Dimension : 324(H) x 178(W) x 30(D)mm



**RESISTANCE**

Range	Resolution	Accuracy
6kΩ	0.001kΩ	±1.0% of rdg + 3 digits
60kΩ	0.01kΩ	
600kΩ	0.1kΩ	
6MΩ	0.001MΩ	
<b>POWER</b>	<b>AAA 1.5V X 3</b>	

**CL-2054**



**Features:**

- 10uA high Resolution
- Large 3 ¾ ( 4000 counts ) LCD Display
- Auto Power OFF (APO)
- Shielded transformer jaw opens to 1.2"

**AC VOLTAGE**

Range	Resolution	Accuracy	
		50/60 Hz	40-1KHz
400V	0.1V	± 1.5% of rdg ± 2 digits	± 2.0% of rdg ± 4 digits

**AC CURRENT**

Range	Resolution	Accuracy	
		50/60 Hz	Wide (400-1KHz)
40mA	10µA	± 1.0% of rdg ± 0.5mA digits	± 4.5% of rdg ± 0.5mA digits
400mA	100µA	± 3.0% of rdg ± 5.0mA digits	± 3.0% of rdg ± 5.0mA digits
4A	1mA	± 4.0% of rdg ± 0.1A digits	± 4.0% of rdg ± 0.1A digits
40A	10mA	± 4.0% of rdg ± 1.0A digits	± 4.0% of rdg ± 1.0A digits
80A	100mA	± 2.5% of rdg ± 1.0A digits	± 3.0% of rdg ± 1.5A digits
80-100A		± 5.0% of rdg ± 1.0A digits	± 5.0% of rdg ± 1.5A digits

**RESISTANCE**

Range	Resolution	Accuracy
40-400Ω	0.1Ω	± 1.0% of rdg ± 2 digits

**CONTINUITY TEST** Threshold 40Ω, Continuity Beeper 2.5KHz

**POWER** 9V (6F22) X 1

- Standard Accessories : Hard Carrying Case, Test Lead, Manual
- Dimension : 209(H) x 43(W) x 30(D)mm

