

Power Clamp Meter

PA-170

HTCTM
INSTRUMENTS

Features:

- Analysis for single phase and balanced 3 phase system
- True RMS Value (Voltage Current)
- Large LCD Display with Backlight
- USB interface
- Min/Max measurement
- True Power/Apparent power/ power factor measurement
- Data Hold/ Auto ranging / Overflow indication/ Auto power Off
- 2.16"(55mm) Jaw opening



Specification :

Function	Range	Accuracy
AC Voltage	15V/100V/300V/750V	$\pm(1.2\%+5)$
AC Current	40A/100A/400A/1000A	$\pm(2\%+5)$
True Power	0.60kW-750kW	$\pm(3\%+5)$
Apparent Power	0.60kVA-750kVA	$\pm(3\%+5)$
Reactive Power	0.60kVAr-750kVAr	$\pm(4\%+5)$ of 15V/1000A else $\pm(4\%+5)$
Power Factor	0.3-1	$\pm(2\%+20)$
Phase Angle	0° -90°	± 1
Frequency	20Hz-200Hz	$\pm(0.5\%+5)$
Energy	1-9999kWh	$\pm(3\%+2)$

- **Standard Accessories:** Test Lead, Gifts Box Carrying Case and 9VBattery,USB cable
- **Dimension** :295(H) x 100(W) x 46(D)mm